

## DECLARATION OF CONFORMITY

No GTW\_500\_001

Unique identification code of the product-type: GTW-500  
 Intended use/es: P+S geotextile for protection and separation  
 Manufacturer: Comercial Projar, S.A.  
 C/ La Pinaeta, s/n  
 46930 Quart de Poblet, Valencia  
 Systems of AVCP: 4  
 Standard / Guideline: FLL Green Roof Guidelines, 2018

Declared performance/s:

	Unit	Performance	Tolerance	Standard
Tensile strength MD	kN/m	10	- 1,3	EN ISO 10319
Tensile strength CMD	kN/m	15	- 1,9	EN ISO 10319
Elongation MD	%	45	± 15	EN ISO 10319
Elongation CMD	%	40	± 15	EN ISO 10319
CBR puncture	N	3000	- 300	EN ISO 12236
Dynamic perforation test (Cone drop test)	mm	1,8	+ 0,45	EN ISO 13433
Characteristic opening size $O_{90}$	µm	79	± 20	EN ISO 12956
Water permeability normal to the plane VI <sub>150</sub>	l/m <sup>2</sup> s	62	- 24	EN ISO 11058
Durability	Must be covered in 1 day after installation. Predicted to be durable for a minimum 5 years in natural soils with 4<pH<9 and soil temperatures <25°C			EN 13252 Annex B

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of conformity is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ana Llopis, Product Solution Manager

S-46930 Valencia, 10.12.2022.

Comercial Projar S.A.  
 A-46217923  
 C/. La Pinaeta, s/n  
 Pol. Ind. Quart de Poblet  
 46930 Quart de Poblet (Valencia)  
 Tel. 96 393 74 90 Fax 96 192 02 50  
 Signature