

DUPONT™ PLANTEX® PERFORMANCE TAPE



PRODUCT DESCRIPTION & APPLICATION

Double-Sided Adhesive Butyl Sealing Tape consists of a butyl rubber adhesive compound (BK - aggressive tack for porous surfaces) and interliner.

TECHNICAL PERFORMANCE

Compound type / Colour	Double-Sided Butyl Rubber Adhesive / Grey
Standard thickness	1.0 mm
Interliner	release paper
180° Peel Adhesion (ASTM D 1000)	16 N/cm
Probe Tack (ASTM D 2979)	6.0 N
Storage temperature range	+ 5 °C / + 30 °C
External temperature range for application	0 °C / + 35 °C
Service Temperature Range	- 30 °C / + 90 °C

FEATURES AND BENEFITS

- Plantex® Performance Tape has a high immediate tack and excellent adhesion onto Plantex® weed control products, especially Plantex® Platinum and Plantex® Platinum Solar
- The sealing tape must be applied to a clean, dry, smooth and dust-free surface
- In case of porous/uneven supports it's advisable to stabilize the surface
- The quality and the characteristics of the materials remain unaltered for a long period of time. However, it is recommended to use the product within 12 months from production date
- The product must be stored in the original and unopened packaging in a dry and well-ventilated place without direct exposure to UV-light
- Storage and application above the indicated temperature may lead to difficulties in removing the release liner when applying
- The product is not affected by frost

This information corresponds to our current knowledge on the subject. It is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for any application other than the application as specified herein. This information may be subject to revision as new knowledge and experience becomes available. Since we cannot anticipate all variations in actual end-use conditions, DuPont makes no warranties and assumes no liabilities in connection with any use of this information for applications other than the application as specified herein. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right. Product safety information is available on request. This data sheet is a printed document and is valid without signature.

DuPont de Nemours (Luxembourg) S.à r.l.
L-2984 Luxembourg

www.plantexpro.dupont.com

Language: English
Effective date: 15.07.2017