

DECLARATION OF PERFORMANCE

No PR_Drain_25_001

Unique identification code of the product-type: PR-DRAIN-25
 Intended use/es: Drainage geocomposite, geospacer core (PS) used for the functions: D
 Manufacturer: Comercial Projar, S.A.
 C/ La Pinaeta, s/n
 46930 Quart de Poblet, Valencia
 Manufacturing plant: E46
 Systems of AVCP: 2+
 Standard / Guideline: EN 13252:2016
 Certification body: SKZ - Testing GmbH, 1213

Declared performance/s:

		Performance	Tolerance	Test method
Compressive strength	kN/m ²	325	±60	EN ISO 25619-2
Tensile strength	kN/m	NPD		
Water flow capacity* 20kPa MD i=1	l/ms	4,64	-	EN ISO 12958
Durability	Must be covered in 1 day after installation. Predicted to be durable for a minimum 5 years in natural soils with 4<pH<9 and soil temperatures <25°C			EN 13252 Annex B

*water flow under the sheet

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of conformity is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ana Llopis, Product Solution Manager

S-46930 Valencia, 23.01.2023.

Comercial Projar S.A.
 A-46217928
 C/. La Pinaeta, s/n
 Pol. Ind. Quart de Poblet
 46930 Quart de Poblet (Valencia)
 Tel. 96 159 74 80 - Fax 96 192 02 50

Terméknév (cikkszám):
 Produkt Name (Art.Nr.):
 Product name (Art.Nr.):

PR-DRAIN-25 (QS7)

Drénlemez | Drainplatte | Drainage board - 1995x1003x25 mm

Palettacímke
 Palette Etikett
 Pallet Label

ALAPADATOK | BASISINFORMATIONEN | BASIC INFORMATION

Terméktípus Produkttyp Product type	Anyag Material Material	Rendeltetés Funktion Function
Drainage geocomposite	PS	Drénlemez tetőrendszerekhez Drainplatte für Dachsysteme Drainage board for roof systems

TELJESÍTMÉNY | LEISTUNG | PERFORMANCE

	Nyomószilárdság ¹ Druckfestigkeit ¹ Compressive strength ¹	Nyomószilárdság ² Druckfestigkeit ² Compressive strength ²	Vízáramlási kapacitás* Wasserleitvermögen* Water flow capacity*
	kN/m ²		l/ms
Teljesítmény Leistung Performance	325	775	4,64
Tűrésérték Toleranz Tolerance	±60	±80	-
Szabvány Prüfverfahren Test method	EN ISO 25619-2		EN ISO 12958
Tartósság Beständigkeit Durability			1: üresen unverfüllt unfilled
Várható tartósság legalább 5 év, ter mészetes talajokban, amelyek esetén 4<pH<9, és a talajhőmérséklet 25°C alatti. Beständig für mindestens 5 Jahre in natürlichen Böden mit 4<pH<9 und Bodentemperatur <25°C. Predicted to be durable for a minimum 5 years in natural soils with 4<pH<9 and soil temperatures <25°C.			2: feltöltve 8%-os összenyomódásnál verfüllt bei 8% Stauchung filled at 8% compression
Be kell fedetni 1 napon belül a telepítés után. Innerhalb von 1 Tag nach der Verlegung zu bedecken. Must be covered in 1 day after installation.			

RAKLAP | PALETTE | PALLET

Mennyiség Menge Quantity	250 db/raklap, Stk/Pal, pcs/pal; 500 m ² /raklap, Palette, pallet
Nettó tömeg Netto Gewichte Net weight	680 kg/raklap, Palette, pallet
Felülettömeg Flächengewicht Surface weight	1.36 kg/m ²
Gyártás (név) Produktion (Name) Production (name)	
Rendelészám Bestellnummer Order number	
Raklapszám Palettenummer Pallet number	
Dátum Datum Date	
Aláírás Unterschrift Signature	

Comercial Projar S.A.
 A-46217923
 C/ La Pineta, s/n
 Pol. Ind. Quart de Poblet
 46930 Quart de Poblet (Valencia)
 Tel. 96 159 74 80 - Fax 96 192 02 90