

## DECLARATION OF PERFORMANCE

No PR\_Drain\_40\_001

Unique identification code of the product-type: PR-DRAIN-40  
 Intended use/es: Drainage geocomposite, geospacer core (HIPS) used for the functions: D  
 Manufacturer: Comercial Projar, S.A.  
 C/ La Pinaeta, s/n  
 46930 Quart de Poblet, Valencia  
 Manufacturing plant: E46  
 Systems of AVCP: 2+  
 Standard / Guideline: EN 13252:2016  
 Certification body: SKZ - Testing GmbH, 1213

Declared performance/s:

		Performance	Tolerance	Test method
Compressive strength	kN/m <sup>2</sup>	280	±40	EN ISO 25619-2
Tensile strength	kN/m	NPD		
Water flow capacity* 20kPa MD i=1	l/ms	5,34	-0.08	EN ISO 12958
Durability	Must be covered in 1 day after installation. Predicted to be durable for a minimum 5 years in natural soils with 4<pH<9 and soil temperatures <25°C			EN 13252 Annex B

\*water flow under the sheet

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of conformity is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ana Llopis, Product Solution Manager

S-46930 Valencia, 23.01.2023.



**Comercial Projar S.A.**  
 A-46217923  
 C/. La Pinaeta, s/n  
 Pol. Ind. Quart de Poblet  
 46930 Quart de Poblet (Valencia)  
 Tel. 96 159 74 80 - Fax 96 192 02 50



Terméknév (cikkszám):  
 Produkt Name (Art.Nr.):  
 Product name (Art.Nr.):

# PR-DRAIN-40 (QS8)

Drénlemez | Drainplatte | Drainage board - 1995x1003x40mm

Palettacímke  
 Palette Etikett  
 Pallet Label

## ALAPADATOK | BASISINFORMATIONEN | BASIC INFORMATION

Terméktípus Produkttyp Product type	Anyag Material Material	Rendeltetés Funktion Function
Drainage geocomposite	HIPS	Drénlemez tetőrendszerekhez Drainplatte für Dachsysteme Drainage board for roof systems

## TELJESÍTMÉNY | LEISTUNG | PERFORMANCE

	Nyomószilárdság <sup>1</sup> Druckfestigkeit <sup>1</sup> Compressive strength <sup>1</sup>	Nyomószilárdság <sup>2</sup> Druckfestigkeit <sup>2</sup> Compressive strength <sup>2</sup>	Vízáramlási kapacitás* Wasserleitvermögen* Water flow capacity*
	kN/m <sup>2</sup>		l/ms
Teljesítmény Leistung Performance	280	625	5,34
Tűrésérték Toleranz Tolerance	±40	±80	-0,08
Szabvány Prüfverfahren Test method	EN ISO 25619-2		EN ISO 12958
Tartósság Beständigkeit Durability			1: üresen   unverfüllt   unfilled
Várható tartósság legalább 5 év természetes talajokban, amelyek esetén 4<pH<9, és a talajhőmérséklet 25°C alatti. Beständig für mindestens 5 Jahre in natürlichen Böden mit 4<pH<9 und Bodentemperatur <25°C. Predicted to be durable for a minimum 5 years in natural soils with 4<pH<9 and soil temperatures <25°C.			2: feltöltve 8%-os összenyomódásnál verfüllt bei 8% Stauchung filled at 8% compression
Bekelltemetni 1 napon belül a telepítés után. Innerhalb von 1 Tag nach der Verlegung zu bedecken. Must be covered in 1 day after installation.			

## RAKLAP | PALETTE | PALLET

Mennyiség   Menge   Quantity	180 db/raklap, Stk/Pal. pcs/pal; 360 m <sup>2</sup> /raklap, Palette, pallet
Nettó tömeg   Netto Gewichte   Net weight	705 kg/raklap, Palette, pallet
Felülettömeg   Flächengewicht   Surface weight	1,9 kg/m <sup>2</sup>
Gyártás (név)   Produktion (Name)   Production (name)	
Rendelészám   Bestellnummer   Order number	
Raklapszám   Palettenummer   Pallet number	
Dátum   Datum   Date	
Aláírás   Unterschrift   Signature	

Comercial Projar S.A.

A-46217923

C/. La Pinaeta, 3

Pol. Ind. Quart de Poblet

46930 Quart de Poblet (Valencia)

Tel: 96 159 74 80 - Fax 96 192 02 50

projar