

DECLARATION OF PERFORMANCE

No PR_Drain_60_001

Unique identification code of the product-type: PR-DRAIN-60
 Intended use/es: Drainage geocomposite, geospacer core (HIPS) used for the functions: D
 Manufacturer: Comercial Projar, S.A.
 C/ La Pinaeta, s/n
 46930 Quart de Poblet, Valencia
 Manufacturing plant: E46
 Systems of AVCP: 2+
 Standard / Guideline: EN 13252:2016
 Certification body: SKZ - Testing GmbH, 1213

Declared performance/s:

		Performance	Tolerance	Test method
Compressive strength	kN/m ²	129	±40	EN ISO 25619-2
Tensile strength	kN/m	NPD		
Water flow capacity* 20kPa MD i=1	l/ms	13,73	-0,08	EN ISO 12958
Durability	Must be covered in 1 day after installation. Predicted to be durable for a minimum 5 years in natural soils with 4<pH<9 and soil temperatures <25°C			EN 13252 Annex B

*water flow under the sheet

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of conformity is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ana Llopis, Product Solution Manager

S-46930 Valencia. 23.01.2023.


 signature
Comercial Projar S.A.
 A-46217923
 C/ La Pinaeta, s/n
 Pol. Ind. Quart de Poblet
 46930 Quart de Poblet (Valencia)
 Tel. 96 159 74 80 - Fax 96 192 02 50


Terméknév (cikkszám):
 Produkt Name (Art.Nr.):
 Product name (Art.Nr.):

PR-DRAIN-60 (QS9)

Drénlemez | Drainplatte | Drainage board - 1940x940x60 mm

Palettacímke
 Palette Etikett
 Pallet Label

ALAPADATOK | BASISINFORMATIONEN | BASIC INFORMATION

Terméktípus Produkttyp Product type	Anyag Material Material	Rendeltetés Funktion Function
Drainage geocomposite	HIPS	Drénlemez tetőrendszerekhez Drainplatte für Dachsysteme Drainage board for roof systems

TELJESÍTMÉNY | LEISTUNG | PERFORMANCE

	Nyomószilárdság ¹ Druckfestigkeit ¹ Compressive strength ¹	Vízáramlási kapacitás* Wasserableitvermögen* Water flow capacity*
	kN/m ²	l/ms
Teljesítmény Leistung Performance	129	13,73
Tűrésérték Toleranz Tolerance	±40	-0,08
Szabvány Prüfverfahren Test method	EN ISO 25619-2	EN ISO 12958

Tartósság Beständigkeit Durability

Várható tartósság legalább 5 év, természetes talajokban, amelyek esetén 4 < pH < 9, és a talajhőmérséklet 25°C alatti.
 Beständig für mindestens 5 Jahre in natürlichen Böden mit 4 < pH < 9 und Bodentemperatur < 25°C.
 Predicted to be durable for a minimum 5 years in natural soils with 4 < pH < 9 and soil temperatures < 25°C.

Be kell tenni 1 napon belül a telepítés után. Innerhalb von 1 Tag nach der Verlegung zu bedecken. Must be covered in 1 day after installation.

RAKLAP | PALETTE | PALLET

Mennyiség Menge Quantity	145 db/raklap, Stk/Pal, pcs/pal; 263,9 m ² /raklap, Palette, pallet
Nettó tömeg Netto Gewichte Net weight	590 kg/raklap, Palette, pallet
Felülettömeg Flächengewicht Surface weight	2,22 kg/m ²
Gyártás (név) Produktion (Name) Production (name)	
Rendelészám Bestellnummer Order number	
Raklapszám Palettenummer Pallet number	
Dátum Datum Date	
Aláírás Unterschrift Signature	

Comercial Projar S.A.

A-46217923

C/ La Pinaeta, s/n

Pol. Ind. Quart de Poblet

46930 Quart de Poblet (Valencia)

Tel. 96 159 74 80 - Fax 96 192 02 50

Drain_60_001

projar